



AIR CONDITIONING SYSTEM WITH HEAT PUMP FUNCTION / BREEZONIC

ENJOY THE BREEZE

The very powerful Breezonic air conditioning units are ultramodern rooftop systems. They are equipped with a heat pump function and the innovative inverter technology ensures very quiet, constant operation and a low energy consumption. This is made possible by a variable-speed compressor. Operating with a superior sustainable refrigerant R32, compared to the industry standard refrigerant R410A. These units have been developed for maximum efficiency. With eight operating settings, they adapt perfectly to your individual comfort requirements.

There are two versions available:

The Breezonic Performance provides 2.5 kW of cooling and 2.4 kW of heat output.

The strongest model, Breezonic Performance Plus provides 3.5 kW of cooling and 3.6 kW of heat output.



Scan the QR code
to learn more.

PRODUCT BENEFITS:

- Combined powerful cooling and heating via heat pump
- Extremely silent operation and low energy consumption with variable speed compressor
- Very low current and soft-ramp up
- High efficiency
- Uses the more environmentally friendly refrigerant R32
- Very flat design
- Night mode for quiet operation during sleep
- Eco mode for low energy consumption
- Very fast interior cooling using the turbo cooling function



Air distribution box**

OTHER FEATURES :

- Various control options via touch screen on interior panel (ADB), remote control, App (via Bluetooth) or central HMI possible
- Very slim and stylish design of the interior panel with integrated, dimmable LED lighting
- Multiple function settings available: Heating, Cooling, Automatic, Timer, Turbo, Eco, De-Humidification, Fan only, 3 fan speed settings
- Operating temperature from -7 to +52 °C



Touch Panel**

App*

Touch HMI

Remote Control**

4 different control options: Via touchscreen on the air distribution box, via app (via Bluetooth), via remote control or via a central control unit (e.g. EasyStart Touch).

SEGMENTS:



TECHNICAL DATA:

BREEZONIC		BREEZONIC PERFORMANCE		BREEZONIC PERFORMANCE PLUS	
Voltage	V	230 V AC / 50 Hz			
Cooling performance	W	2500		3500	
Heating performance	W	2400		3600	
Weight Rooftop / Air Distribution Box (ADB)	kg	32.9 / 2.8		35.1 / 2.8	
Current max. average cooling	A	4,1		6,5	
Current max. average heating	A	4,2		6,0	
Refrigerant		R32			
Dimensions of roof unit (L x B x H)	mm	1051 x 698 x 250			
Dimensions of interior unit (L x B x H)	mm	503 x 482 x 45			
Hatch / Roof openings	mm	360 x 360 / 400 x 400			
Roof thickness	mm	25 - 75			
Communication interfaces		CI- Bus, RV-C, Bluetooth (app)			
Control unit		Control via app, touch screen control panel on device and via remote control (as optional accessory)			
Part number unit		29 0218 41 0001		29 0218 41 0002	
Part number Air Distribution Box (ADB)		29 0218 11 0001			
Part number remote control		29 0248 27 0001			

* Free Breezonic app available in the Apple and Google Play Appstore; Smartphone shown is not included in the scope of delivery

** Optional accessories