



A WORLD OF COMFORT

 Eberspächer



**Slim and elegant:**  
the air distribution box with  
touchscreen and dimmable light  
in cool white and warm white.

EBERSPÄCHER CLIMATE  
CONTROL SYSTEMS INTERNATIONAL GMBH  
EBERSPÄCHERSTRASSE 24  
73730 ESSLINGEN, GERMANY

PHONE: +49 (0) 711 939-00  
INFO@EBERSPÄECHER.COM  
WWW.EBERSPÄECHER-CLIMATE.COM



BREEZONIC

## ENJOY THE BREEZE

The new air conditioning system with heat pump function: provides cold and warm air, is efficient and whisper-quiet.

| [EBERSPÄECHER-MOTORHOMES.COM](http://EBERSPÄECHER-MOTORHOMES.COM)

# THE NEW EBERSPÄCHER BREEZONIC

## POWERFUL AIR CONDITIONER WITH HEAT PUMP FUNCTION

The very powerful Breezonic air conditioning units are ultra-modern rooftop systems. They are equipped with a heat pump function and the innovative inverter technology ensures very quiet, constant operation and a low energy consumption. This is made possible by a variable-speed compressor. These units have been developed for maximum efficiency. With eight operating settings, they adapt perfectly to your individual comfort requirements.

### ADVANTAGES

- Combined high-performance cooling and heating via heat pump
- Extremely quiet operation and low energy consumption thanks to a variable-speed compressor
- Very low power consumption due to smooth start-up
- Uses the more sustainable refrigerant R32
- Modern design
- Night mode for quiet operation while you sleep
- Eco mode for low energy consumption
- Very fast interior cooling thanks to turbo cooling function
- Operating temperature from -7 to +52°C



4 different control options: Via touchscreen on the air distribution box, via app (via Bluetooth), via remote control or via a central control unit (e.g. EasyStart Touch).

\* Free Breezonic app available in the Apple and Google Play Appstore; Smartphone shown is not included in the scope of delivery  
\*\* Optional accessories

### PERFORMANCE PERFORMANCE PLUS

Current voltage	V	230 V AC / 50 Hz	
Cooling capacity	W	2,500	3,500
Heat output	W	2,400	3,600
Weight of roof/air distribution box	kg	32.9 / 2.8	35.1 / 2.8
Current max. average cooling	A	4.1	6.5
Current max. average heating	A	4.2	6.0
Refrigerant		R32	
Dimensions of the roof unit (L × W × H)	mm	1,051 × 698 × 250	
Indoor unit dimensions (L × W × H)	mm	503 × 482 × 45	
Hatch/roof openings	mm	360 × 360 / 400 × 400	
Roof thickness (Standard)	mm	25 – 75	
Communication interfaces		CI-Bus, RV-C, Bluetooth (App)	
Control unit		Control via app, touchscreen control panel on the device, touch HMI or by remote control (as an optional accessory)	
Part number unit		29 0218 41 0001	29 0218 41 0002
Part number air distribution box		29 0218 11 0001	
Remote control part number		29 0248 27 0001	